Tool set for hub/bearing





Tool set for compact wheel hub/bearing unit

UNIVERSAL FROM Ø 62 TO Ø 85 mm

HYDRAULIC CYLINDER 17 T






Complete Kit 323 034 000

- This UNIVERSAL Govoni kit is the solution to pull out and mount the new Hubs with new Bearing Unit HBU2 (assembed unit including hubs and bearings)
- Thanks to its features, it can works on bearings from a diameter of Ø62 mm to Ø85 mm.
- QL) The main features of the kit are efficiency and fast use, endurance and heavy duty components.

BEARINGS	BRAND
Ø 62	Audi, VW
Ø 66	Skoda
Ø 68	Citroën, Renault
Ø 72	Audi, Seat
Ø 75	Mitsubishi, Smart
Ø 78	Ford, Volvo
Ø 82	Ford, Volvo
Ø 85	4x4, SUV

The main advantages are:

- UNIVERSAL disassembling system (suitable to all the models)
- Use directly on the vehicle
- Safety use in assembling/disassembling (no break or damage of the hub)
- it reduces working time of 25% compared to common tools



Components

323029001 Thrust bell



323029012 Counterthrust nut

Components



M20X1.5 Spindle -323029004 HEX. 15 mm



323034007 Pushing bush Ø62 mm



323029012 Nut



323034008 Pushing bush Ø66 mm



HEX. 30 mm thrust block 323029015 bearing



323034009 Pushing bush Ø68 mm



Tool set for hub/bearing

Made in Italy

Components

323029020 Pushing bush Ø72 mm



323029009 Pushing bush Ø82 mm

Components



323034004 Pushing ring \varnothing 62 mm



323034005 Pushing bush Ø85 mm



323034003 Pushing ring Ø66, Ø68 mm



323029006 Pushing ring Ø82, Ø85 mm



Pushing ring Ø72, Ø75, 323029016 Ø78 mm



323029010 Pulling ring



Pulling bush Ø72, Ø75, Ø78, Ø82, Ø85 mm 323029022



323029021 Spacers Ø 18X9



Pulling bush Ø62, Ø66, 323034010 Ø68 mm



323029014 Washers Ø 18X3



323034006 Pushing bush $\varnothing 75~\text{mm}$



822084000 Screw M12X55




323029018 Pushing bush Ø78 mm



Hydraulic cylinder 17 T -270025000 Stroke 43 mm




REMOVAL



Innovative system allows to settle the diameter of the pulling rings thanks to middle spacers that fits to the diameters of the bearing to remove

INSTALLATION



Pulling rings system - when closed - allows to push around the external diameter of the bearing, in the undercut granting the perfect operation of the product, avoiding the break of the hub



GO OPERATING DIRECTLY INTO **VEHICLES**

